



Xitanium LED downlight and spotlight drivers

XI 20W WH 0.15-0.5A 54V TD/IS CL 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	540 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Current (Min)	150 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	Yes
Temperature	
T-Case Lifetime (Max)	75 ℃
T-Case Maximum (Max)	85 ℃

Controls and Dimming	
Dimmable	DALI
Dimming Range	100-1 %
Mechanical and Housing	
Product Length	200 mm
Housing	WH Independent
Overall width	75 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.204 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC
	certificate RCM compliance
Output Current Set Options	DALI, NFC
Product Data	
Order product name	XI 20W WH 0.15-0.5A 54V TD/IS CL 230V
Full product name	XI 20W WH 0.15-0.5A 54V TD/IS CL 230V
Full product code	871869959379700

Datasheet, 2024, October 10 data subject to change

Xitanium LED downlight and spotlight drivers

Order code	929001649806
Material Nr. (12NC)	929001649806
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699593797

Numerator - Packs per outer box 20		
EAN/UPC - Case	8718699593803	



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.