



Xitanium LED downlight and spotlight drivers

Xitanium 36W/m 0.15-1.05A 48V MC 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information		T-Case Maximum (Max)	
Lighting Technology	LED		85 °C
Operating and Electrical		Controls and Dimming	
Output Current Ripple (Max)	4 %	Dimmable	Wireless Dim
Output Current (Max)	1050 mA	Control Interface	Wireless
Open Circuit Voltage (DC) (Max)	60 V	Dimming Range	100-1 %
Output Power (Max)	36 W	Mechanical and Housing	
Output Power (Min)	6 W	Product Length	97 mm
Output Current (Min)	150 mA	Housing	Mini 97x43x30 2p2p NFC
Output Voltage (Max)	48 V	Overall length	97.2 mm
Output Voltage (Min)	24 V	Overall width	43 mm
Protection class IEC	Safety class I/II	Overall height	30 mm
System characteristics		Dimensions (Height x Width x Depth)	30 x 43 x 97 mm
Central DC Operation	Yes	Ingress protection code	IP20 [Finger-protected]
YellowDot ready	No	Net Weight (Piece)	0.100 kg
Temperature		Approval and Application	
T-Case Lifetime (Max)	75 °C	Isolation Classification	Class I and Class II
		Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance

Xitanium LED downlight and spotlight drivers

Output Current Set Options	NFC
Product Data	
Order product name	Xitanium 36W/m 0.15-1.05A 48V MC 230V
Full product name	Xitanium 36W/m 0.15-1.05A 48V MC 230V
Full product code	692234192146900
Order code	929002133006

Material Nr. (12NC)	929002133006
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6922341921469
Numerator - Packs per outer box	20
EAN/UPC - Case	6922341921476

