



Xitanium LED drivers – full programmable

Xi FP 75W 0.2–0.7A SNLDAE 230V C133 sXt

Our Xitanium full programmable Xtreme LED drivers are designed to deliver the highest performance, reliability and configuration possibilities. The portfolio offers both stand-alone and remote dimming protocols to further decrease energy use with the latest LED technologies. The proven Xtreme technology ensures maximum robustness and protection for a very long lifetime. These drivers are the preferred choice for demanding applications such as outdoor and industry. Configuration of these drivers can be done via both the universal DALI or with SimpleSet, which is the latest technology for reliable, fast and easy altering and reading out of settings.

Product data

General Information		Protection class IEC	
Nominal lifetime	100,000 hour(s)	Safety class I/II	
Lighting Technology	LED	Surge Protection (Common/Differential) Surge protection level until 10 kV	
Operating and Electrical		System characteristics	
Output Current Ripple (Max)	4 %	Central DC Operation	No
Maximum Efficiency at Full Load	91.3 %	YellowDot ready	No
Output Current (Max)	700 mA	Temperature	
Open Circuit Voltage (DC) (Max)	220 V	T-Case Lifetime (Max)	70 °C
Inrush Current Peak (Max)	43 A	T-Case Maximum (Max)	80 °C
Output Power (Max)	75 W	Controls and Dimming	
Inrush Current Width to 50% of Peak	260 µs	Dimmable	Yes
Diagnostics	True	Dimming Range	100-10 %
Output Power (Min)	2.5 W	D4i compliant	No
Output Current (Min)	50 mA	DynaDimmer	Yes
Output Voltage (Max)	150 V		
Output Voltage (Min)	50 V		

Xitanium LED drivers – full programmable

Constant light output	Yes
-----------------------	-----

Mechanical and Housing

Product Length	133 mm
Housing	C133_FP
Overall length	133 mm
Overall width	77 mm
Overall height	39.5 mm
Dimensions (Height x Width x Depth)	40 x 77 x 133 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.560 kg

Approval and Application

Isolation Classification	Class I and Class II
Approval Marks	CCC certificate CE marking CB compliance ENEC certificate

Output Current Set Options	SimpleSet, DALI
----------------------------	-----------------

Product Data

Order product name	Xi FP 75W 0.2-0.7A SNLDAE 230V C133 sXt
Full product name	Xi FP 75W 0.2-0.7A SNLDAE 230V C133 sXt
Full product code	87195143447400
Order code	929002872806
Material Nr. (12NC)	929002872806
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514344747
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514344754

